



**FOG CONTROL DEVICE  
PERMIT NO. \_\_\_\_\_**

In compliance with the provisions, terms, and conditions of the City of Hobart Sewer User Ordinance, as amended, and also with applicable provisions of Federal, State, and local law and regulations,

**[Company Name  
&  
Address]**

is authorized to discharge wastewater from activities classified by Standard Industrial Classification No. 5812 from premises located at the above address to the Hobart Sanitary District's wastewater collection system in accordance with effluent limitations, monitoring requirements, and conditions set forth in this permit and The Municipal Code of the City of Hobart ("HMC").

This permit shall become effective \_\_\_\_\_ and authorization to discharge shall expire at midnight on \_\_\_\_\_. The permittee must reapply for continuation of this permit 60 days prior to the expiration date.

Signed this \_\_\_\_\_ day of \_\_\_\_\_, \_\_\_\_\_.

\_\_\_\_\_  
Coordinator  
Hobart Sanitary District

## **PERMIT REQUIREMENTS**

Effluent shall consist of domestic wastewater meeting the effluent requirements outlined in the HMC. Oil and grease concentration shall not exceed 60 mg/L.

### **Proper Operation and Maintenance**

The permittee shall at all times maintain the FOG control device in good working order and operate, as efficiently as possible, all facilities and systems of treatment and control installed or used by the permittee to achieve compliance with the terms and conditions of this Permit.

Each facility shall clean or pump out its grease control device according to the following criteria:

1. When the settled solids layer equals the invert of the outlet pipe (typically eight inches in depth), or;
2. When the total volume of captured grease and solid material displaces more than twenty-five percent (25%) of the capacity of the interceptor, or;
3. When the interceptor is not retaining or capturing oils and greases.

The frequency of cleaning and pump outs shall be determined by each facility. A regular maintenance schedule is recommended.

FOG control devices shall be inspected on a weekly basis.

Fats, oils, and grease removed in the course of device cleaning shall be disposed of in a manner so as to prevent any pollutants from entering the sewer system.

### **Record Keeping Requirements**

Permittee must maintain records of device cleaning on HSD maintenance forms attached to this Permit.

### **Right to Inspect**

Grease control devices shall be inspected by HSD as it deems necessary to assure compliance with the requirements of this Permit. HSD personnel shall have the right to enter the premises at all reasonable times for the purpose of inspection, observation, records examination, measurement, sampling, and testing in accordance with this Permit.

### **Bypass of FOG Control Device**

Bypass of the FOG control device is prohibited, unless:

- a. bypass was necessary to prevent loss of life, personal injury, or severe property damage; or
- b. the HSD approved an anticipated bypass, considering its adverse effects, if the permittee, knowing in advance of the need for a bypass, submitted prior notice to HSD of the bypass, in writing, at least ten (10) days before the bypass; or
- c. the bypass does not cause effluent limitations to be exceeded.

# UNDER-SINK GREASE TRAP MAINTENANCE FORM

## For \_\_\_\_\_

Name/Address of Facility

**Grease trap must be cleaned or pumped out on a regular basis to maintain proper operation.**

Failure to maintain the grease trap or to complete and submit this form to HSSWD may result in fines being assessed, mandatory pump out by a grease hauling contractor, or mandatory installation of an in-ground grease interceptor.

By signing below, I certify that all information below is correct, that all the wastewater was removed from the grease trap, and that the wastewater was disposed of properly (as solid waste or hauled off-site by a licensed waste hauler) and was not returned to any part of the sanitary sewer system.

DATE	CLEANED BY (print name)	SIGNATURE	DISPOSAL (circle one)	
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site
			Solid Waste	Off-Site

This completed form is due semi-annually to HSD at the address above.

## UNDERGROUND GREASE TRAP MAINTENANCE FORM

For \_\_\_\_\_

Name/Address of Facility

**Grease trap must be pumped out on a regular basis.** Failure to maintain the grease trap or to complete and submit this form to HSSWD may result in fines being assessed and mandatory pump outs by a grease hauling contractor.

By signing below, I certify that all information below is correct, that all the wastewater was removed from the grease trap, and that the wastewater was disposed of properly (hailed off-site by a licensed waste hauler) and was not returned to any part of the sanitary sewer system.

<i>DATE</i>	<i>HAULING COMPANY (name and address)</i>	<i>SIGNATURE</i>